



Helm Instrument Company, Inc.
361 West Dussel Drive
Maumee, Ohio 43537 USA
419/ 893-4356
Fax: 419/ 893-1371
www.helminstrument.com

HM-1734-WM SPECIFICATIONS

Voltage Range	10-28.8V dc
Type of input	Strain Gage (350 ohm, 700 ohm)
Input Impedance	5.11 meg. ohm
Display Resolution	Up to .0025% of full scale
Overall Module Accuracy	.01% of full scale
Module Update Time	Software selectable from 1ms to 1000ms
Number of Channels	2 (isolated)
A/D Conversion Method	Successive Approximation - 24 bit
Normal Mode Rejection: (between +/- input)	116DB CMRR
Amplifier Bandwidth	200 kHz
Calibration	Software Selectable
Vibration Filtering	Programmable
Isolation	500 VDC continuous between inputs and chassis ground, and between input and backplane
LED indicators	2 LED's for Power and Alarm
Recommended Cable	Strain Gage Cable (Helm part number 6117)
Operating Temperatures	0°C to 60°C (32°F to 140°F)
Hazardous Environment Classification	Class 1 Division 2 Hazardous Environment
Pointbus Current	5V @ 72ma
External Power	24V @ 19.5ma
Dimensions	2.21H x 0.47W x 2.97L (Millimeters 56H x 12W x 75.5L)